PRODUCT DATASHEET

NiMH Battery Charger (CHQA)

European Region

Download Instructions (multilingual)

Page 01 | Page 02 | Page 03

Rapide Charger

HI-TECH

 Red and Green LEDs for each pair of batteries show charging status and alert for bad batteries



CONVENIENT

 Charge 2 or 4 AA or AAA batteries at the same time



ADVANCED

- Two Stage Charge
- Primary Battery Detection



Before Using Your Charger:

INCLUDES

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Product Detail:

Designation: Rapide Charger

Color: Black and Silver

Charging Current: 2 or 4 "AA" 600mA

2 or 4 "AAA" 350mA

Slow Charge: "AA" 350mA

"AAA" 175mA

Trickle Charge: 0-70mA

Charging Times:BatteryCapacityEstimated(estimated)(NiMH)(mAh)(time)

(NiMH) (mAh) (time)

AA 2500-2650 5.0-5.3 hrs

AA 1300-2400 2.6-4.8 hrs

AAA 850-1000 2.9-3.4 hrs

Shutoff Mechanism: Delta V and Temperature Detection

and Timer Control

Delta V Detection 0-15mV per channel (2 cells)

Temp. Detection 41-45°C

Max Timer Control 2 or 4 "AA" 6 hours

2 or 4 "AA" 3.5 hours

Charger Input: 100-240V AC 50/60Hz

Weight (charger): 138.8 grams

Dimensions (mm): 34.7 x 112.0 x 69.5 (H x L x W)

Safety Features: Delta V Charging Cut Off

Short Circuit and Reverse Polarity Protection

Safety Timer to Prevent Over Charge Primary and Bad Battery Detection

NOTE: Batteries must be charged in pairs.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.

